

BACKLIT PHOTO PAPER 150g

The satin matt paper is the best choice for light boxes for indoor and outdoor use and convinces with its brilliant colours. The reproduction is homogeneous and cloudless in transmission. euromedia Backlit Photo Paper 150g is particularly easy to print on, dries quickly and is suitable for Solvent, Latex and UV printers. The PEFC certified paper is dimensionally stable and resistant to condensation. It is thus an environmentally friendly alternative to backlit films.

The special feature of this product: It provides two functions in one. euromedia Backlit Photo Paper 150g can be used both in transmitted light and, as a poster or photo paper, with reflected light. The satin matte coating guarantees reproduction of bright colours and excellent contrast without annoying reflections.

Processing tips	SPECIFICATIONS	
Wear our euromedia Allrounder Gloves to prevent fingerprints when applying the finished graphics. The storage and processing of the material should in principle take place under equal conditions (see Storage). Alternatively, place the material minimum 24 hours before printing in the immediate area of the printer to prepare it for these conditions prior to printing. We recommend that you allow the print to fully dry for minimum 72 hours before finishing. For the long-term preservation of the print and the image quality, it is recommended to laminate. The material is suitable for hot and cold laminates.	Material	Backlit-Photo Paper
	Thickness (microns)	130
	Surface	Satin matt
	Weight (g/m²)	150
	Whiteness	108
	Opacity	95,50%
	Tensile strength	MD 7,6 kN/m / CD 3,4 kN/m
	Tearing strength	MD 500mN / CD 690mN
	Outdoor durability	up to 1 month (in light box)
	Others	Brightness (print side):91,8% (D65, ISO 2469, TAPPI) Print side is outside
	Shelf life	3 years

Dimensions	
Roll Width	1370mm/54" - 1600mm/63"
Roll Length	60m

Storage

Ideal conditions are a relative humidity of 35-65% and a temperature of 15-25 ° C. We recommend storing the material in the original case. Store the rolls always together with the label and batch number. Without batch number, no claims can be accepted.

Compatibility of machines and ink

Media is suitable for all (eco) solvent, UV curable inks and latex digital printers with heating system.

IMPORTANT NOTICE - WARRANTY

The information and recommendations contained in this Product Information Sheet, as well as technical advice otherwise given by representatives of our Company, whether verbally or in writing, are based on our present knowledge and believed to be accurate. However, no guarantee regarding their accuracy is given as we cannot cover or anticipate every possible application of our products and because processing methods, printing inks and other materials vary. Our products are manufactured with high quality raw materials, advanced technology and equipment, guaranteed by serious and scientific quality control systems. All products are warranted to be free of defects as of materials and manufacture at the time of shipment and meet their specifications. Should there is any product defect caused by the manufacturing process, compensation will be limited within the specific product cost. Our policy of continuous improvement might make some of the information contained in this Product Information Sheet out of date and users are requested to ensure that they follow current recommendations. TSEKMERES B.SA is not responsible for the performance of this material for a given application. The users of the materials must perform their own testing to determine the suitability of the product for their specific application.