UFABRIK

Universal Backlit Textile

Substrate	DIN 60001,ASTM D7641	100% Polyester
Weave		Woven
Yarn	DIN EN 2060,ASTM D1907	150D*2X150D*2
Weight approx.	ISO536	180 gsm, 5.3oz/yd
Opacity	ISO2471	80±5
Light Transmittance		57%±3
Fire retardancy	DIN 4102-1 B1 EN13501-1	
Application		indoor
Width		1600, 2600, 3200, 5050 mm / 63, 102, 126, 199 inches
Roll length		50, 100 m / 55, 109 yds
Type of ink	DS TRANSFER UV	
Environmental elements	No PVC · Low-VOCs Emission · No Heavy Metal · DOP Free	

Advantages

- Water tight
- Water repellent
- Crease and bruise resistance
- Cold cut
- PVC Free
- REACH compliant

Applications

- Lightboxes
- Blacklit Frames
- Tension Frames
- Inflatables
- Display Systems
- Soft Signage

Coated side – UV / Latex printing is the inside of the roll – Uncoated side – Dye sublimation transfer printing
(If printing direct dye sublimation, please test due to ink variants) is the outside of the roll

ΤΣΕΚΜΕΡΕΣ Β. ΑΕ, Λ. Αθηνών 352 Περιστέρι 121 36 Αθήνα, Τηλ. 210 57 82 400, info@tsekmeres.gr, www.tsekmeres.gr, ΑΡ. ΓΕΜΗ: 609801000

TSEKMERES
GRAPHIC SYSTEMS
ΑΠΟ ΤΟ 1968